

HVT







THE VCT ALTERNATIVE

Technical Specifications

Sizes

Size	Thickness	Pcs/Carton	Sqft/Carton	Lbs/Carton
18 in x 18 in	2.5 mm	16 pcs	36 sqft	31 lbs

Testing

Test Item		Standard	Results
Level of use		ISO 10874	33, Heavy commercial
Static load limit		ASTM F970	2,000 psi
Squareness & Straightness		ISO 24342 ASTM F2055	Passes No deviation, ≤0.1mm
Flexibility		ASTM F137	Passes
Dimensional stability		ASTM F2199	Passes
Resistance to chemicals		ASTM F925	Passes, No defects
Resistance to light		ASTM F1515	Passes
Resistance to heat		ASTM F1514	Passes
Fire resistance		ASTM E648	Passes
Smoke density		ASTM E662	Passes
Slip resistance		ASTM E303	Passes
Indoor air quality			Low VOC, Floor Score certified
Dynamic Coefficient of Friction		ANSI A326.3	0.43


Caution

Condition in at least 19°C (67°F) or the normal temperature of the room where the product is to be laid, for at least 48 hours before installing. Cartons must be stacked less than 5 high and tiles removed 30 minutes before use. The site conditions must be maintained during installation and for at least 48 hours after completion. Evo Floors, LLC will not accept claims where these instructions have not been followed.

Manufacturing

ISO 9001 Quality Management System
 ISO 14001 Environmental Management System
 OSHAS 18001 Occupational Health and Safety Management System

Certification



Please visit www.evofloors.com for detailed installation / maintenance guides and technical information.