



# PRIZM

## HRC

HYBRID  
RESILIENT  
CARPET





Reflect | 601  
Opaque | 608  
Ray | 628

### Most Hygienic



Patented dual protection coating system meets environmental standards for anti-bacterial and anti-microbial performance  
Safe and Clean  
Easy Cleaning and Maintenance

### Most Stable + Uniquely Layered Structure



The most reliable EvoCore structure for outstanding dimensional stability.  
Consistent product thickness allows for mixing and matching HRC™ patterns

### Tough + Waterproof



Superior wear resistance and waterproof function for commercial applications

### Fray-Proof



Clean-cut finishing to prevent fraying even when tiles are cut into unique shapes during installation



Opaque | 608



# HRC

# PRIZM COLLECTION

## HYBRID RESILIENT CARPET

HRC™ offers the best of both worlds where the comfort of carpet meets the functionality of resilient flooring.

## EVO LAYERS

EvoCore layering technology provides dimensional stability and consistent thickness. Easy to clean and maintain, the coated surface layers are scratch and slip-resistant, waterproof, and tough enough for commercial applications.

Micro-Reinforced Polymers (MRP™)  
Coated Surface Layer



Highly protective barrier against dirt, bacteria,  
stains, scuffs and chemicals

Premium Woven Fabric Layer

Secondary MRP™ Protective Layer

Acoustical Layer

Stabilizing Layer

Anti-Curling Layer

HRC™ PRIZM collection's uniquely creative design can spotlight an area while still easily blend into its surroundings. This upbeat pattern scatters parallelograms of differing shades onto a plain jacquard fabric of similar color schemes.

Enrich your space with HRC™ PRIZM, a lively, modern collection that is stylish and design forward while also catering to universal taste.

Refract | 609  
Radiant | 613





Opaque | 608  
Radiant | 613  
Diffuse | 605



**SAFE**  
Certified non-toxic,  
phthalate-free,  
and fiberglass-free  
fabric



**QUICK**  
Quick & easy  
installation



**EASY**  
Minimal cleaning time  
and low maintenance



**SILENT & SOFT**  
Soft surface that  
absorbs sound



**NON-SLIP**  
D11, slip-resistance  
with the woven fabric  
textured surface



**COLORFAST**  
Non-fading properties  
retain gorgeous  
original colors over  
time



Photon | 607  
Radiant | 613  
Ray | 628

**EVO**  
FLOORS



# HRC

HYBRID RESILIENT CARPET  
PRIZM COLLECTION



Reflect | 601



Diffuse | 605



Photon | 607



Opaque | 608



Refract | 609



Radiant | 613



Spectrum | 627



Ray | 628




\* Each carton contains a random set of pieces, which present different parts of the pattern.

50 cm x 50 cm  
(19.87 in x 19.87 in)  
Tile Size




3.0 mm  
Thickness


Installation Methods




Monolithic



Brick



Mix & Match HRC: Prizm square tiles with HRC: Woven Collection plank tiles for the most unique design possibilities!



The printed images may not be an accurate reproduction of the products' actual colorways. We strive to offer an authentic representation, but images may vary according to press run and digital displays. These images are intended as a guide only. Visit [evofloors.com](http://evofloors.com) for samples and more information.





# HRC

HYBRID RESILIENT CARPET












## PRIZM

### Technical Specifications

#### Sizes

Size	Thickness	Pcs/Carton	Sqft/Carton	Lbs/Carton
50 cm x 50 cm (19.87 in x 19.87 in)	3.0 mm	16 pcs	43.03 sqft	44.08 lbs

#### Testing

Test Item		Standard	Results
Level of use		ISO 10874	33, Heavy commercial
Fraying		ISO 10833	Frayproof
Thermal resistance		ISO 8302	0.02m²K/W
Castor chair resistance		ISO 4918	No damage
Dimensional stability		ISO 23999 EN 986	≤ 0.10% ( Norm: ≤ 0.25% ) Passed
Fire resistance		EN 13501-1	Bfl -s1
Indoor air quality			Low VOC (floor score certified)
Underfloor heating		EN 12524	Suitable
Light fastness		ISO 105-B02	≥ 6
Slip resistance		ASTM E303 EN 13893	R11, Suitable for wet and dry environments DS
Flexibility		ISO 24344	Passed
Impact sound insulation		ISO 10140-3	9dB
Body Voltage		EN 1815	≤ 2KV
Squareness & Straightness		ISO 24342 ASTM F2055	No deviation ≤ 0.01 in
Residual indentation		ISO 24343-1 ASTM F1914	≤ 0.1mm < 8%
Resistance to chemicals		ISO 26987 ASTM F925	No Defects No Defects

#### Caution

Condition in at least 19°C (67°F) or the normal temperature of the room where the product is to be laid, for at least 48 hours before installing. Cartons must be stacked less than 5 high and tiles removed 30 minutes before use. The site conditions must be maintained during installation and for at least 48 hours after completion. Evo Floors, LLC will not accept claims where these instructions have not been followed.


#### Certification



GREENGUARD  
SOLUTIONS  
Sustainable  
Solutions



OEKO-TEX®  
CONFIDENCE IN TEXTILES  
STANDARD 100



Please visit [www.evofloors.com](http://www.evofloors.com) for detailed installation / maintenance guides and technical information.