



HVT

HYBRID VINYL TILE

2.5mm | 20mil

RESISTANCE TO CHEMICALS

ASTM F925

5 minute ratings

24 hour ratings

| staining agent | surface dulling | surface attack | color change | surface dulling | surface attack | color change |
|---------------------------|--------------------|-------------------|-----------------|--------------------|-------------------|-----------------|
| 5% acetic acid | 0 | 0 | 0 | 0 | 0 | 0 |
| 70% isopropyl alcohol | 0 | 0 | 0 | 0 | 0 | 0 |
| mineral oil | 0 | 0 | 0 | 0 | 0 | 0 |
| 5% sodium hydroxide | 0 | 0 | 0 | 0 | 0 | 0 |
| sulfuric acid | 0 | 0 | 0 | 0 | 0 | 0 |
| 5% hydrochloric acid | 0 | 0 | 0 | 0 | 0 | 0 |
| 5% ammonia | 0 | 0 | 0 | 0 | 0 | 0 |
| 5.25% sodium hypochlorite | 0 | 0 | 0 | 0 | 0 | 0 |
| 5% phenol | 0 | 0 | 0 | 0 | 0 | 0 |
| bleach | 0 | 0 | 0 | 0 | 0 | 0 |
| gasoline | 0 | 0 | 0 | 0 | 0 | 0 |
| olive oil | 0 | 0 | 0 | 0 | 0 | 0 |
| noble brio cream cleanser | 0 | 0 | 0 | 0 | 0 | 0 |
| ecolab milkro quat | 0 | 0 | 0 | 0 | 0 | 0 |
| kerosene | 0 | 0 | 0 | 0 | 0 | 0 |

0 - no change
1 - slight change
2 - moderate change
3 - severe change



EVOFLOORS.COM